

## DC6000 Series Door Closers

## Features

### DC6200 - Multi-Sized DC6400 - Sizes 1-6, half size adjustable

#### Features

##### Spring Power

DC6200 closers: multi-sized; fully adjustable sizes 1 through 6.  
DC6400 closers: sizes 1 through 6; half-size adjustability.  
For recommended sizes, see page 14.

##### Handing

Non-handed.

##### Body

Cast-iron case with seamless cold headed steel spring tube.

##### Arm

Standard: heavy-duty forged steel.  
Arm options pages 8-10.

##### Spindle

Cold headed heat-treated steel.

##### Piston

Precision machined, heat-treated steel.

##### Springs

Chrome silicon wire.

##### Valves

Latching speed valve standard.

Closing speed valve standard.

Multiple backcheck location valve and backcheck intensity valve standard.

Delayed action valve optional. Delayed action preset for 20 seconds. Between 90° and 70° for all mountings. To order specify M71.

##### Seals

"O" rings.

##### Fluid

Standard: high lubricity extreme temperature hydraulic fluid.

##### Degree of Opening

Up to full 180° opening standard for regular, top jamb and parallel arm mountings, conditions permitting.

##### Power Adjustment Arm Bracket

15% adjustment standard.

##### Cover

Standard: non-metallic full cover.  
Optional: slim cover; specify M76.  
Optional: full metal cover; specify M73 x hand.

##### Mountings

Standard: regular and top jamb.  
Optional mountings available; see Mountings, page 6.

##### Mounting Bracket

QUIK-INSTALL™ mounting bracket standard.

##### Fasteners

Standard: self drilling screws.  
Optional: sex nuts and bolts (SNBs); specify M54.

##### Corrosion Protection

Painted protective coating on all metal surfaces for use in corrosive environments. To order specify M75.

##### Security Package

Includes heavy-duty parallel or regular arm, full metal cover and security Torx® machine screws. Specify M87 x arm x hand.

##### Warranty

Ten-year limited warranty. Refer to Corbin Russwin price book for details.

##### Finishes

Standard painted finishes

Old Designation	Description	Specify
USP	Primed	600
SBL	Silver Aluminum	689
LBL	Dark Bronze	690
DBL	Light Bronze	691
FBL	Black	693
GBL	Satin Brass	696
Plated finishes available on arms and full cover* or full metal cover.		
US3	Bright Brass	605
US4	Satin Brass	606
US9	Bright Bronze	611
US10	Satin Bronze	612
US26	Bright Chromium Plated	625
US26D	Satin Chromium Plated	626

For split finish of closer cover and arm, specify cover finish first, then arm finish (e.g., DC6200 x 625 x 689).

\*Full cover available in 605, 606, 625 and 626 only.

### Certification/Compliance



#### Barrier-Free Code Compliance

The DC6000 Series Door Closers listed below conform to the 5 lbf.

maximum door opening force requirement for non-fire-rated interior hinged doors, according to:

#### Americans with Disabilities Act (ADA)

Complies with the Accessibility Guidelines for Buildings and Facilities, Section 4.13.11

#### ANSI

Meets A156.4, Grade 1.

Meets A117.1.

DC6200	DC6412
DC6210	DC6421
DC6220	DC6401
DC6411	

These door closers are certified by Corbin Russwin Architectural Hardware to comply with the above standards when properly installed and (if applicable) adjusted, in regular arm, parallel arm and top jamb mountings.

#### UL / ULC / UL10c

Listed for fire and cycle requirements.