

DICTATOR type 1600

Enclosed model for normal doors.

DICTATOR door checks noiselessly control the closing of doors. The door check will ensure, that the door will be held firmly closed and will not slam when shut.

The 1600 model being completely closed, is ideal for clean area installations such as hospitals, service shelters and in the food industry. When mounted on the door, the 1600 is unobtrusive. All fixing screws are hidden.

The DICTATOR 1600 is available in chrome finish as standard, and stainless steel finish for use in external or humid conditions.

Fixing the DICTATOR 1600 is effortless. Simply lift the hinged door check housing, then using the screws provided, secure the door check in a central position at the top of the door at about 40 cm. out of the closing side of the door.



DICTATOR 1600 with hook 1009



1011 Low hook
for doors recessed
10 - 20 mm.



1009 High hook
(standard) for
flush doors -4 /
+14 mm.



1013 Extra high
hook for doors
projecting 10 - 30
mm.

In Stainless steel only available with hook 1009.

Technical details

Types of doors

Left and right opening, projecting flush and recessed

Closing force (measured at the door check)

Approx. 20, **50N(standard with this type)** or 80N

Damping characteristic

Progressive, with speed adjustment.

Damping fluid

Silicone

Contents

Door check complete with hook and fixing screws.

Material

Bright chromium plated
Satin chromium plated
Stainless Steel
Bright gold (brass)
White (RAL 9010), Grey (RAL 9006) or Chocolate brown (RAL 8017)
Other RAL colors on application

Packing

Per piece, 8 pcs./set, 16 pcs./half-combi, 32 pcs./combi

DICTATOR type 1600 standard available in the following finishes:



[[Fitting](#)] [[Dimensions](#)]