ELECTRICAL OPERATING CHARACTERISTICS

1400 SERIES

VOLTAGE	AMPS	OHMS	VAC INT.	VAC CONT.	VDC INT.	VDC CONT.	SPECIFY
8-16 VAC OR 3-6 VDC	Use Ohms Law	3.6	YES	NO	YES	NO	-01
12 VAC OR 12 VDC	.150 .200	55.0	YES	NO	YES	YES	-05
24 VAC OR 24 VDC	.080 .110	215.0	YES	NO	YES	YES	-08

3400 SERIES

VOLTAGE	AMPS	OHMS	VAC INT.	VAC CONT.	VDC INT.	VDC CONT.	SPECIFY
12 VDC	.240	50.3	NO	NO	YES	YES	-06
24 VDC	.110	190.9	NO	NO	YES	YES	-09

1500 SERIES

VOLTAGE	AMPS	OHMS	VAC INT.	VAC CONT.	VDC INT.	VDC CONT.	SPECIFY
8-16 VAC OR 3-6 VDC	Use Ohms Law	3.6	YES	NO	YES	NO	-01
12 VAC OR 12 VDC	.150 .200	55.0	YES	NO	YES	YES	-05
24 VAC OR 24 VDC	.080 .110	215.0	YES	NO	YES	YES	-08

1700 AND 1800 SERIES

VOLTAGE	AMPS	онмѕ	VAC INT.	VAC CONT.	VDC INT.	VDC CONT.	SPECIFY	SERIES
8-16 VAC OR 3-6 VDC	Use Ohms Law	16.0	YES	NO	YES	NO	-01	1700
12 VAC OR 12 VDC	.460 .685	16.0	YES	NO	YES	NO	-04	1700
12 VDC	.250	48.0	NO	NO	YES	YES	-05	1700
24 VAC OR 24 VDC	.380 .570	42.0	YES	NO	YES	NO	-07	1700
24 VDC	.140	170.0	NO	NO	YES	YES	-08	1700
8-16 VAC OR 3-6 VDC	Use Ohms Law	13.4	YES	NO	YES	NO	-01	1800
12 VAC OR 12 VDC	.160 .240	50.0	YES	NO	YES	NO	-04	1800
12 VDC	.240	50.0	NO	NO	YES	YES	-05	1800
24 VAC OR 24 VDC	.100 .130	185.0	YES	NO	YES	NO	-07	1800
24 VDC	.130	185.0	NO	NO	YES	YES	-08	1800

2400, 1900 AND 3900 SERIES

2400, 1300 AND 3300 OLITICS											
VOLTAGE	AMPS	OHMS	VAC INT.	VAC CONT.	VDC INT.	VDC CONT.	SPECIFY	SERIES			
12 VAC OR 12 VDC	.190 .260	45.1	YES	NO	YES	YES	-05	2400			
24 VAC OR 24 VDC	.110 .150	157.7	YES	NO	YES	YES	-08	2400			
12 VAC OR 12 VDC	.120 .180	67.0	YES	NO	YES	YES	-05	1900			
24 VAC OR 24 VDC	.075 .100	235.0	YES	NO	YES	YES	-08	1900			
12 VDC	.240	50.0	NO	NO	YES	YES	-06	3900			
24 VDC	.100	235.0	NO	NO	YES	YES	-09	3900			

Intermittent use: not to exceed 10 seconds. Continuous use: for a period longer than 10 seconds to indefinite.

6

Voltage +/- 10%

7/02